www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET **PENOSIL Premium Nail&Fix Interior 915**

Date: 12.02.13 Version nr.: 1 Revised:

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier: PENOSIL Premium Nail&Fix Interior 915

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Used for the installation of wooden or PVC slats on bricks, chip-board, aluminium, galvanized iron, steel or concrete; installation of wooden thresholds, door jambs, profiles and panels. Also suitable for gluing expandable polystyrene and plaster profiles, decorative slats, and ceramics. Elements will have a rigid connection, which is why the adhesive is not suitable for moving connections. Do not use for underwater works or in areas that are in permanent contact with water.

1.3. Details of supplier of the safety data sheet:

Krimelte Ltd 13619 Tallinn Suur-Paala 10 Estonia Tel. +372 605 93 00 Fax: (+372) 605 93 15 112

1.4. Emergency telephone number:

2. Hazards identification

2.1. Classification of the substance or mixture According to 67/548/EC





Xn Harmful R11 Highly flammable R36 Irritating to eyes R38 Irritating to skin

F Highly flammable



N Environmental hazard

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment R62 Possible risk of impaired fertility

R65 Harmful: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

Health

May cause sensitization in contact with skin, eyes, respiratory organs and skin irritation. Harmful through inhalation, in contact with skin and when

indested. Do not let into drains and groundwater. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment Highly flammable

Environment

Fire 2.2. Label elements 2.2.1 Hazard symbol:



F Highly flammable Xn Harmful 2.2.2 Hazardous ingredients: No ingredients



N Environmental hazard

SAFETY DATA SHEET PENOSIL Premium Nail&Fix Interior 915

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium Nail&Fix Interior 915

2.2.3 R-phrases

R11 Highly flammable

R36 Irritating to eyes

R38 Irritating to skin

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment R62 Possible risk of impaired fertility

R65 Harmful: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

2.2.4 S-phrases

S2 Keep out of the reach of children

S9 Keep container in a well-ventilated place

S16 Keep away from sources of ignition - No smoking

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

S61 Avoid release to the environment. Refer to special instructions/safety data sheet

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container

2.3. Other hazards High vapour concentration may cause irritation, head ache and dizziness.

Toxicology data: hexane inhalation 5000 ppm 10 min may cause central nervous system damage.

3.Composition/information on ingredients

3.1. Substances

Classification of substances

CAS-nr.	Chemical name	Content Classification		sification	
		Max.		According Directive 67/548/EEC	According Regulation 1272/2008 (CLP)
-	Mineral fillers	30	%	-	-
110-54-3	Hexane	30	%	F R11 Xn R38 R48/20 R62 R65 R67 R51/53	Flam. Liq.2: H225 Asp. Tox. 1: H304 Skin Irrit. 2: H315 Repr. 2: H361 STOT SE 3: H336 STOT RE 2: H373 Aqua Chronic 2: H411
-	Resin	30	%	-	-
-	Synthetic rubber				
128-37-0	antioxidant				

4. First aid measures

4.1 Description of first aid measures

Inhalation:	Move the exposed person to fresh air. Seek medical attention and show product label.			
Skin contact:	Wash off with plenty of soap and water. Remove contaminated clothing.			
	Seek medical attention if irritation or symptoms persist.			
Contact with eyes:	Rinse eyes immediately with plenty of water, keeping the eye open.			
-	Seek medical attention.			
Ingestion:	Do not induce vomiting. Seek medical attention and show product label.			
4.2. Most important symptoms and effects, both acute and delayed				
Inhalation	Harmful and irritating to respiratory organs.			
Skin contact	May be irritating to skin.			
Contact with eyes	May be irritating to eyes			
Ingestion	Harmful to digestive			
SAFETY DATA SHEET	č			
PENOSIL Premium Nail&Fix Interior	915			

2/6

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium Nail&Fix Interior 915

4.3. Indication of any immediate medical attention and special treatment needed As a general rule, and in all cases of doubt or when symptoms persist, always seek medical attention.

As a general rule, and in all cases of doubt of when symptoms persist, always seek medic

5. Fire fighting measures

5.1 Extinguishing media

5.1.1. Suitable extinguishing media:

Use extinguishing media appropriate the surrounding fire conditions. Use as appropriate: water spray, dry extinguishing media, foam and carbon dioxide.

5.1.2 Unsuitable extinguishing media:

5.2. Special hazards arising from the substance or mixture Hazardous decomposition products:

No specific recommendations.

- CO, easily flammable hydrocarbons, smoke and vapour
- **5.3. Advice for fire-fighters** No specific recommendations.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear protective clothing, goggles and protective chemical resistant gloves. Avoid contact with skin and eyes.

6.2 Environmental precautions:

Prevent the spread of flammable vapours. Do not let product into drains and ground water. The waste must be handled in accordance with legal requirements.

6.3 Methods and material for containment and cleaning up

Cured material can be removed mechanically, surfaces can be washed. Uncured material is soluble in the water. The waste must be handled in accordance with legal requirements. Wash contaminated surfaces with water. Do not let into drain system.

7. Handling and storage

7.1 Precaution for safe handling:

7.1.1. Protective measures

Ensure good ventilation. Keep away from source of ignition. Avoid contact with eyes and skin. Make use of protective goggles and protective chemical resistant gloves.

7.1.2. Advice on general occupational hygiene

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep in a cool, dry, well-ventilated area. Keep the carefully closed cornet at the temperature from +5° C to +30° C, self-life min. 12 months.

7.3. Specific end use(s) Used for the installation of wooden or PVC slats on bricks, chip-board, aluminium, galvanized iron, steel or concrete; installation of wooden thresholds, door jambs, profiles and panels. Also suitable for gluing expandable polystyrene and plaster profiles, decorative slats, and ceramics. Elements will have a rigid connection, which is why the adhesive is not suitable for moving connections. Do not use for underwater works or in areas that are in permanent contact with water.

8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit value

AineCAS-No.Exposure typeExposure limit valueHexane110-54-3TWA176 mg/m³
50 ppm

8.2. Exposure controls

8.2.1. Appropriate engineering controls

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium Nail&Fix Interior 915

Ensure adequate ventilation, especially in confined areas.

8.2.2. Individual protection measures, such as personal protective equipment

Eye/face protection: During the work make use of protective goggles

Skin protection: During the work make use of protective chemical resistant gloves

Respiratory protection: Use the product only in well-ventilated rooms.

8.2.3. Environmental exposure controls Do not let into sewer system or environment. The waste must

be handled in accordance with legal requirements.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Appearance	Paste
	Colour	Brown
	Odour	Light oil odour
	рН	Not applicable
	Melting point / freezing point	68 – 69 °C Hexane
	Boiling point	Not relevant
	Flash point	-23 °C
	Evaporation rate	Not applicable
	Flammability	Not applicable
	Explosion limits	Not applicable
	Vapor pressure	Upper: 7.5 % Lower: 1,2 % Hexane
	Vapor density	Not applicable
	Relative density	1.16 g/cm³/+20 °C
	Solubility in water	No
	Solubility in other solvents	Not relevant
	Partition coefficient: n-octanol/water	Not applicable
	Auto-ignition temperature	Not applicable
	Decomposition temperature	Not applicable
	Viscosity	Not applicable
	Explosive properties	Not applicable
	Oxidizing properties	Not applicable
9.2. C	Other information	Lack of data

10. Stability and reactivity

10.1. Reactivity
 The mixture is not reactive under recommended storage and handling conditions (see section 7).
 10.2. Chemical stability
 The mixture is stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions Combustion

10.4 Conditions to avoid: source of ignition

10.5. Incompatible materials: oxidizing agents, acids

10.6. Hazardous decomposition products: CO, easily flammable hydrocarbons, smoke and vapour

11. Toxicological information

11.1. Information on toxicological effects

11.1.1. Substances

11.1.1.1. The relevant hazard classes for which information shall be provides, are:

(a) Acute toxicity

	Hexane
Acute Oral toxicity	LD50 (rat): 24 mg/kg
Acute Dermal toxicity	LD50 (rabbit): 2000 mg/kg

www.penosil.com

Irritating to skin and mucosa.

Irritating to respiratory organs.

Lack of data

Lack of data Lack of data

Lack of data

Lack of data

In contact with eyes, product may irritate.

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET **PENOSIL Premium Nail&Fix Interior 915**

Acute Inhalation toxicity

LC50: >5000 ppm

- (b) Skin corrosion / irritation (c) Serious eye damage / irritation
- (d) Respiratory or skin sensitization
- (e) Germ cell mutagenicity
- (f) Carcinogenicity
- (g) Reproductive toxicity
- (h) STOT-single exposure
- (i) STOT-repeated exposure

12. Ecological information

12.1. Toxicity

	Hexane
Toxicity to fish	LC50 /48h/: > 1000 microg/l
Toxicity to aquatic invertebrates	Lack of data
Chronic toxicity to fish	Lack of data
Toxicity to bacteria	Lack of data
12.2. Persistence and degradability	Cured product is not degradable.

- 12.2. Persistence and degradability
- 12.3. Bio-accumulative potential:
- 12.4. Mobility in soil:
- 12.5. Results of PBT and vPvB assessment:
- 12.6. Other adverse effects

Not likely Not likely Lack of data Lack of data

13. Disposal considerations

13.1. Waste treatment methods 13.1.1. Product / Packaging disposal: The product and packages must be handled in accordance with national and local requirements. Clean packages can be reused. 13.1.2. Waste treatment options: 13.2. Additional information No specific recommendations.

14 Transport information

	///		
14.1 UN number		UN 1133	
14.2 Packing Group		II	
14.3 Road ADR	UN 1133 hazard class 3	3 Adhesive, consists flammable liquids	
14.4 Railway RID		UN 1133 Adhesive, consists flammable li	quids
14.5 Transport by sea GGVS	ee/IMDG-Code	UN 1133 Adhesive, consists flammable li	quid
14.6 Air transport ICAO-TI/IA	TA-DGR	UN 1133 Adhesive, consists flammable li	quids

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Not applicable 15.2. Chemical safety assessment Chemical safety assessment is not needed, because product includes non-hazardous substances.

16. Other information

- 16.1. Date of preparation of the latest version of the SDS Written in the beginning of the safety data sheet.
- 16.2. Abbreviations and acronyms
- TWA: Time Weighted Average
- LC50: Lethal Concentration Medium
- EC50: effective Concentration Medium

SAFETY DATA SHEET

PENOSIL Premium Nail&Fix Interior 915

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium Nail&Fix Interior 915

STOT: Specific target organ toxicity PBP: Persistent, bioaccumulativ and toxic

vPvB: very persistent very bioaccumulative

Asp. Tox. 1: Aspiration Toxicity Category 1

Flam. Liq. 2: Flammable Liquid Category 2

Repr. 2: Reproductive toxicity, Category 2

Skin Irrit. 2: Skin Irritation Category 2

STOT SE 3: Specific target organ toxicity Single Exposure Category 3

STOT RE 2: Specific target organ toxicity Repeated Exposure Category 2

Aqua Chronic 2: Aquatic Chronic- Category 2

16.3. Key literature references and sources of data

The safety data sheet meets the requirements of the European Parliament and Council Regulation (EC) No.1907/2006 and the Chemicals Act of the Republic of Estonia and regulation No 130 of Minister of Social Affairs.

16.4. Classification and classification procedure used for mixtures

16.5. Relevant R-phrases and/or H-statements (specified in clause 3)

According Directive 67/548/EEC

R11 Highly flammable

R36 Irritating to eyes

R38 Irritating to skin

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R62 Possible risk of impaired fertility

R65 Harmful: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

According Regulation 1272/2008 (CLP)

H225 Highly flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage the organs through prolonged or repeated exposure

H411 Toxic to aquaticlife with long lasting effects

16.6. Training advice

16.7. Further information

No specific recommendations.

No specific recommendations.