www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET **PENOSIL Premium StoneFix 827**

Date: 24.01.2013 Version nr.: 1 Revised:

1. Identification of the mixture and of the company/undertaking

1.1. Product identifier: **PENOSIL Premium StoneFix 827**

1.2. Relevant identified uses of the mixture and uses advised against: Foam is used for installation of stone blocks on buildings.

1.3. Details of supplier of the safety data sheet:

Krimelte Ltd 13619 Tallinn Suur-Paala 10 Estonia Tel. +372 605 93 00 Fax: (+372) 605 93 15 112

1.4. Emergency telephone number:

2. Hazards identification

2.1. Classification of the mixture According to 67/548/EC



Harmful (Xn)



Extremely flammable (F+)

R12	Extremely flammable		
R20	Harmful by inhalation		
R36/37/38	Irritating to eyes, respiratory system and skin		
R40	Limited evidence of a carcinogenic effect		
R42/43	May cause sensitization by inhalation and skin contact.		
R48/20	Harmful: danger of serious damage to health by prolonged		
	exposure through inhalation		
The vapor will irritate throat and lungs. Vapor is dangerous in huge			

amounts. Irritating to eyes. Occasionally, contact produces skin allergy.

May cause long-term adverse effects in the aquatic environment.

Health

Environment Fire

2.2. Label elements

- 1. Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- 2. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

The propellant is inflammable and explosive.

3. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

2.2.1 Hazard symbol:



Harmful (Xn) 2.2.2 Hazardous ingredients: 2.2.3 R-phrases

Extremely flammable (F+) Consists isocyanate. See information applied by the manufacturer. R12 Extremely flammable R20 Harmful by inhalation

SAFETY DATA SHEET **PENOSIL Premium StoneFix 827**

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium StoneFix 827

	R36/37/38 R40 R42/43 R48/20	Irritating to eyes, respiratory system and skin Limited evidence of a carcinogenic effect May cause sensitization by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged
		exposure through inhalation
2.2.4 S-phrases	S2	Keep out of the reach of children
	S9	Keep container in a well-ventilated place
	S16	Keep away from sources of ignition No smoking
	S 23	Do not breathe gas/vapor
	S33	Take precautionary measures against static discharges.
	S36/37	Wear suitable protective clothing and gloves
	S45	In case of accident or if you feel unwell, seek medical advice
		immediately (show the label where possible).
	S51	Use only in well-ventilated areas
2.3. Other hazards	No data ava	

3.Composition/information on ingredients

3.1. Substances. Classification of substances

CAS-no. REACH No.	Chemical name	Con	tent		Classification
		Max.		According Directive 67/548/EEC	According Regulation 1272/2008 (CLP)
9016-87-9 01-2119457014-47	Diphenylmethane-4´,4 ´-diisocyanate	45	%	Xn; R20 R36/37/38 R42/43 R40 R48/20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2, H319 Resp. Sens. 1; H334 Skin Sens.1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373
1244733-77-4 01-2119486772-26	Phosphoric trichloride, reaction products with propylene oxide	15	%	Xn R22	Acute Tox. 4: H302
75-28-5	Isobutane	6	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280
74-98-6	Propane	3	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280
115-10-6 01-2119472128-37	Dimethylether	5	%	F+; R12	Flam. Gas 1; H220 Press. Gas H280

4. First aid measures

4.1 Description of first aid measures

Inhalation:	Move the exposed person to fresh air. Seek medical attention.
Skin contact:	Wash off with plenty of soap and water. Remove contaminated clothing.
	Seek medical attention if irritation or symptoms persist.
Contact with eyes: medical	Rinse eyes immediately with plenty of water, keeping the eye open. Seek attention.
Ingestion: show	Do not induce vomiting or give water to drink. Seek medical attention and product label.
	•

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium StoneFix 827

4.2. Most important symptoms and effects, both acute and delayed Inhalation Irritating to respiratory system.

InhalationISkin contactIContact with eyesI

Irritating to skin. Irritating to eyes

Ingestion

May cause suffocation and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

As a general rule, and in all cases of doubt or when symptoms persist, always seek medical attention.

5. Fire fighting measures

5.1 Extinguishing media

5.1.1. Suitable extinguishing media:

Use extinguishing media appropriate the surrounding fire conditions. Use as appropriate: water spray, dry extinguishing media, foam and carbon dioxide. No specific recommendations.

5.1.2 Unsuitable extinguishing media:

5.2. Special hazards arising from the mixture: Due to heat pressure in the aerosol-can is rising and there is a risk for explosion. In contact with fire product forms toxic fumes. Explosive propellant-air mix can be formed.

5.3. Advice for fire-fighters

No specific recommendations.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear protective clothing, goggles and protective chemical resistant gloves classified under Standard EN374. Avoid contact with skin and eyes. Do not inhale fumes. Use a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387), when you use product in the room which has a poor ventilation

6.2 Environmental precautions: Spillages shall be absorbed by sand or cloths and stored in suitable container, or allow the foam to solidify. The waste must be handled in accordance with legal requirements.

6.3 Methods and material for containment and cleaning up: Fresh foam can be removed with PENOSIL Premium Foam Cleaner, cured foam mechanically or with PENOSIL Premium Foam Remover.

7. Handling and storage

7.1 Precaution for safe handling: During operation, note that the product contains a flammable gas. Keep away from heat. Do not break or burn even after use. Should not be sprayed on a open flame or any incandescent material.

7.1.1. Protective measures: Ensure good ventilation. Keep away from heat. Keep away from sources of ignition - No Smoking. Avoid contact with eyes and skin. Avoid static electricity. Make use of protective goggles and protective chemical resistant gloves classified under Standard EN374.

7.1.2. Advice on general occupational hygiene: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. **7.2. Conditions for safe storage, including any incompatibilities:** Storage: Keep in a cool, dry, well-ventilated area in an upright position away from direct sunlight and other heat sources. Do not store in the direct sunlight and not more than +50 °C. Storage: temperature +5°C to +30 °C.

7.3. Specific end use(s): Foam is used for installation of stone blocks on buildings.

8. Exposure controls/personal protection

8.1 Control parameters. Occupational exposure limit value

Components	CAS-No. / REACH	Type form of exposure	Control parameters
	No.		
Dimethyl ether	115-10-6 / 01-	TWA	1920 mg/m ³
_	2119472128-37-		1000 ppm

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium StoneFix 827

	0001		
Diphenylmethane-	9016-87-9 / 01-	No information	0,05 mg/m ³ 8 hours
4,4'-diisocyanate	2119457014-47		0.005 ppm 8 hours
Propane	74-98-6	No information	Short time: 2000 mg/m ³ , 1100
			ppm
			Long time: 1500 mg/m ³ , 800 ppm
Butane	106-97-8	No information	Short time: 1810 mg/m ³ , 750
			ppm
			Long time: 1450 mg/m ³ , 600 ppm
Phosphoric	1244733-77-4 / 01-	DNEL (short- /long-term	22,4 mg/m ³ / 5,82 mg/m ³
trichloride,	2119486772-26-	exposure by inhalation)	
reaction products	0000	DNEL (short- /long-term	8 mg/kg bw/days / 2,08 mg/kg
with propylene		exposure by skin	bw/days
oxide		contact)	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

8.2.2. Individual protection measures, such as personal protective equipment

Eye/face protection: During the work make use of protective goggles

Skin protection: During the work make use of protective chemical resistant gloves

classified under Standard EN374: protective gloves against chemicals and microorganisms.

Respiratory protection:

Use the product only in well-ventilated rooms. Do not inhale fumes. When using in poorly ventilated area, wear a suitable filter of the mask (ie type A1 in accordance with EN 14387).

8.2.3. Environmental exposure controls Do not let into environment. May cause long-term adverse effects in the aquatic environment.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

	ionnoui proportioo
Appearance	Aerosol
Colour	Pale beige
Odour	Characteristic
рН	Not applicable
Melting point / freezing point	Not relevant
Boiling point	Over +100 °C
Flash point	Below -20 °C
Evaporation rate	Not relevant
Flammability	Above +100 °C
Explosion limits	Low: 2 % vol, high: 10% vol.
Vapor pressure	5 Bar/+20 °C 10 Bar/+50 °C
Vapor density	Not applicable
Relative density	1.1 g/ml/+20 °C
Solubility in water	insoluble
Solubility in other solvents	In acetone soluble
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	+ 200 °C
Viscosity	ca 500 cP/+20 °C
Explosive properties	Contains flammable gases.
Oxidizing properties	Not applicable
9.2. Other information	Lack of data
SAFETY DATA SHEET PENOSIL Premium StoneFix 827	

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET

PENOSIL Premium StoneFix 827

10. Stability and reactivity

10.1. Reactivity: The mixture is not reactive under recommended storage and handling conditions (see section 7).

10.2. Chemical stability: The mixture is stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions In case of fire, the product can create corrosive and hazard gases.

10.4 Conditions to avoid: An aerosol container is under pressure, do not expose to heat. Do not store in the sun, and not more than +50 °C. Do not break or burn even after use. Should not be sprayed on a open flame, or any incandescent material.

10.5. Incompatible materials: No data available

10.6. Hazardous decomposition products: In case of fire, the product can create corrosive and hazard gases.

11. Toxicological information

11.1. Information on toxicological effects

11.1.1. Substances

11.1.1.1. The relevant hazard classes for which information shall be provides, are:

(a) Acute toxicity

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Acute Oral toxicity	Not applicable	LD50 (rat): > 2.000 mg/kg	Not applicable	LD50(female rat): 632 mg/kg LD50(male rat):500- 2000 mg/kg
Acute Dermal toxicity	Not applicable	Not applicable	Not applicable	LD50(male rat):>2000 mg/kg
Acute Inhalation toxicity	LC50 (rat): 164 000ppm Respiratory effects Anaesthetic effects Central nervous system depression narcosis Cardiac irregularities Coma.	LC50 (rat): 490 mg/m ³ 4h Tested substance: Aerosol. Saturated vapour concentration at 25 °C: 0,09 mg/m ³	Not applicable	LC50 (rat): > 7 mg/l 4h

(b) Skin corrosion / irritation

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Skin irritation	Not tested on animals. Classification: Not classified as irritant. Result: No skin irritation. Not expected to cause skin irritation based on expert review of the properties of the substance.	Rabbit. Result: No skin irritation Method: OECD test guide 404	No skin irritation	No skin irritation

(c) Serious eye damage / irritation

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium StoneFix 827

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Eye irritation	Not tested on animals. Classification: Not classified as irritant. Result: No eye irritation Not expected to cause eye irritation based on expert review of the properties of the substance.	Rabbit. Result: No eye irritation Method: OECD test guide 405	No eye irritation	No eye irritation

(d) Respiratory or skin sensitization

	Dimethyl ether	Diphenylmethane-4 ´,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Sensitization	Not tested on animals. Classification: Not a skin sensitizer. Not expected to cause eye irritation based on expert review of the properties of the substance.	Result: May cause sensitization by inhalation and skin contact. Isocyanate vapor may cause asthmatic allergy	No sensitization effect	Lack of information

(e) Germ cell mutagenicity

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Germ cell mutagenicity	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.	Lack of data	Not applicable	OECD 482 Genetic Toxicology: DNA damage and repair, unscheduled DNA Synthesis in Mammalian Cells in vito: negative result

(f) Carcinogenicity

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Carcinogenicity	Animal testing did not show any carcinogenic effects.	Lack of data	Not applicable	LOAEL 99 mg/kg Rat

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium StoneFix 827

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Reproductive toxicity	No toxicity on reproduction May cause cardiac arrhythmia. Rapid evaporation of the liquid may cause frostbite.	Lack of data	Not applicable	LOAEL 99 mg/kg Rat every day. No deaths on that concentration level.

(h) STOT-single exposure Lack of data (i) STOT-repeated exposure Lack of data

12. Ecological information

12.1. Toxicity

	Dimethyl ether	Diphenylmethane-4,4´- diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Toxicity to fish	LC50 /96h/ Poecilia reticulate (guppy): > 4000 mg/l	LC50 /96h/ danio rerio: > 1.000 mg/l Method: OECD test guide 203	Not applicable	LC50 /96h/ Pimephales promelas: 51 mg/l Method: OECD 201 Alga
Toxicity to aquatic invertebrates	EC50 /48h/ Daphnia: > 4000 mg/l LC50 /48h/ Daphnia: 755,5 mg/l	EC50 /24h/ Daphnia magna: > 1.000 mg/l Method: OECD test guide 202	Not applicable	EC50 /24h/ Daphnia magna: 131 mg/l Fresh water Method: ISO 8192
Chronic toxicity to fish	Due to its physical properties, there is no potential for adverse effects.	Lack of data	Lack of data	Lack of data
Toxicity to bacteria	Lack of data	EC50 /3h/ activated sludge: >100 mg/l Method: OECD test guide 209	Lack of data	EC50 /3h/ bacteria: 784 mg/l Method: ISO 8192

12.2. Persistence and degradability

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Persistence and degradability	Method: Closed Bottle test According to the results of tests of biodegradability this product is not readily biodegradable.	Biodegradability 28 days 0 %. Method: OECD test guide 302 C	Not applicable	95 % 64 days OECD 302A Inherent Biodegradability

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET **PENOSIL Premium StoneFix 827**

12.3. Bio-accu	mulative potential:	

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Bioaccumulation	No data available	No data available	Not applicable	BCF 0.8 - 14

12.4. Mobility in soil:

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
Mobility in soil	Koc: 7,759	No data available	Not applicable	No data available

12.5. Results of PBT and vPvB assessment:

	Dimethyl ether	Diphenylmethane- 4,4´-diisocyanate	Isobutane / propane	Phosphoric trichloride, reaction products with propylene oxide
PBT and vPvB	This substance is not considered to be persistent, bio	No data available	Not applicable	PBT : No vPvB : No
assessment	accumulating nor toxic (PBT). The substance is not considered			
	to be very persistent nor very bio accumulating (vPvB).			

12.6. Other adverse effects

Dimethyl ether
Ozone depletion potential: 0 Global warming potential (GWP): 1

13. Disposal considerations

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal:	The product and packages must be handled in accordance with
	national and local requirements. Dirty packages should be
	handled as product waste.

13.1.2. Waste treatment options: 13.2. Additional information

14. Transport information

- 14.1 UN number
- 14.2 Packing Group
- 14.3 Road ADR
- 14.4 Railway RID

14.5 Transport by sea GGVSee/IMDG-Code 14.6 Air transport ICAO-TI/IATA-DGR

Clean foam bottles are recyclable.

No specific recommendations.

1950 Not known Inflammable aerosol Class 2/5F Inflammable aerosol Class 2/5F Aerosol Class 2

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET PENOSIL Premium StoneFix 827

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

15.2. Chemical safety assessment: Chemical safety assessment has been carried out for dimethyl ether and still at work for diphenylmethane-4´,4´-diisocyanate.

16. Other information

16.1. Date of preparation of the latest version of the SDS Written in the beginning of the safety data sheet. 16.2. Abbreviations and acronyms TWA: Time Weighted Average LC50: Lethal Concentration Medium EC50: effective Concentration Medium STOT: Specific target organ toxicity PBP: Persistent, bioaccumulativ and toxic vPvB: very persistent very bioaccumulative LOAEL: Lowest observed adverse effect level BCF: bioconcentration factor DNEL: Derived no effect level Acute Tox.4: Acute Toxicity: inhaled- Category 4 Carc. 2: Carcinogenicity- Category 2 Eye Irrit. 2: Serious eye damage/ eye irritation- Category 2 Resp. Sens. 1: Respiratory sensitization- Category 1 Skin Irrit.2: Skin corrosion/irritation- Category 2 Skin Sens. 1: Skin sensitization- Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure): inhalation- Category 2 STOT SE 3: Specific target organ toxicity (single exposure): inhalation- Category 3 Flam. Gas 1: Flammable Gas- category 1 Press. Gas: Gases under pressure 16.3. Key literature references and sources of data The safety data sheet meets the requirements of the European Parliament and Council Regulation (EC) No.1907/2006 and the Chemicals Act of the Republic of Estonia and regulation No 130 of Minister of Social Affairs. 16.4. Classification and classification procedure used for mixtures 16.5. Relevant R-phrases and/or H-statements (specified in clause 3) According Directive 67/548/EEC R12 Extremely flammable R20 Harmful by inhalation. R22 Harmful if swallowed R36/37/38 Irritating to eyes, respiratory system and skin. R40 Limited evidence of a carcinogenic effect R42/43 May cause sensitization by inhalation and skin contact. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. According Regulation 1272/2008 (CLP) H220 Extremely flammable gas H280 Contains gas under pressure; may explode if heated H302 Harmful if swallowed H315 Cause skin irritation H317 May cause an allergic skin reaction H319 Causes serious eye irritation H332 Harmful if inhaled

SAFETY DATA SHEET

PENOSIL Premium StoneFix 827

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

SAFETY DATA SHEET **PENOSIL Premium StoneFix 827**

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

H351 Suspected of causing cancer

H373 May cause damage to organs through prolonged or repeated exposure if ihaled.

16.6. Training advice

16.7. Further information

No specific recommendations.

No specific recommendations.