www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

## PENOSIL EasyGun Foam All Season

Date: 16.06.2010 Version nr.: 4 Revised: 15.08.2011

## 1. Identification of the mixture and of the company/undertaking

1.1. Product identifier: PENOSIL EasyGun Foam All Season

## 1.2. Relevant identified uses of the mixture and uses advised against:

Foam is used for installation of doors and windows, insulation and fixation of tubes, filling of holes and gaps, fixation of wall panels and roof stones, and for thermal insulation.

Adheres well to most building materials, with the exception of teflon, polyethylene and silicon surfaces. Cured foam is sensitive to UV-light and direct sunlight.

1.3. Details of supplier of the safety data sheet:

Krimelte Ltd 13619 Tallinn Suur-Paala 10 Estonia

Tel. +372 605 93 00 Fax: (+372) 605 93 15

1.4. Emergency telephone number:

### 2. Hazards identification

## 2.1. Classification of the mixture According to 67/548/EC



Harmful Xn.



Extremely flammable (F+)

R12 Extremely flammable R20 Harmful by inhalation

R36/37/38 Irritating to eyes, respiratory system and skin

R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitization by inhalation and skin contact.

R48/20Harmful: danger of serious damage to health by prolonged exposure through inhalation

R53 May cause long-term adverse effects in the aquatic environment

R64 May cause harm to breast-fed babies

Health The vapor will irritate throat and lungs. Vapor is dangerous in huge

amounts. Irritating to eyes. Occasionally, contact produces skin allergy.

**Environment** May cause long-term adverse effects in the aquatic environment. Fire

The propellant is inflammable and explosive.

#### 2.2. Label elements

- 1. Persons already sensitised to diisocyanates may develop allergic reactions when using this
- 2. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- 3. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

2.2.1 Hazard symbol:



SAFETY DATA SHEET PENOSIL EasyGun Foam All Season

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

## PENOSIL EasyGun Foam All Season

Harmful (Xn) Extremely flammable (F+)

2.2.2 Hazardous ingredients: Consists isocyanate. See information applied by the manufacturer.

2.2.3 R-phrases R12 Extremely flammable R20 Harmful by inhalation

R36/37/38 Irritating to eyes, respiratory system and skin Limited evidence of a carcinogenic effect

R42/43 May cause sensitization by inhalation and skin contact.
R48/20 Harmful: danger of serious damage to health by prolonged

exposure through inhalation

R53 May cause long-term adverse effects in the aquatic

environment

R64 May cause harm to breast-fed babies 2.2.4 S-phrases S2 Keep out of the reach of children

S9 Keep container in a well-ventilated place

S16 Keep away from sources of ignition -- No smoking

S 23 Do not breathe gas/vapor

S33 Take precautionary measures against static discharges.

S36/37 Wear suitable protective clothing and gloves

S45 In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

S51 Use only in well-ventilated areas

**2.3. Other hazards** No data available

## 3. Composition/information on ingredients

### 3.1. Substances. Classification of substances

CAS-nr.	Chemical name	Conte	ent		Classification
		Max.		According Directive 67/548/EEC	According Regulation 1272/2008 (CLP)
9016-87-9	Diphenylmethane-4´,4 ´-diisocyanate	40	%	Xn; R20 R36/37/38 R42/43 R40 R48/20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2, H319 Resp. Sens. 1; H334 Skin Sens.1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373
85535-85-9	C14-17, chlorinated paraffin	15	%	N; R50/53 R64 R66	Lact; H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410
75-28-5	Isobutane	8	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280
74-98-6	Propane	4	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280
115-10-6	Dimethylether	4	%	F+; R12	Flam. Gas 1; H220 Press. Gas H280

### 4. First aid measures

## 4.1 Description of first aid measures

Inhalation: Move the exposed person to fresh air. Seek medical attention.

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

## PENOSIL EasyGun Foam All Season

Skin contact: Wash off with plenty of soap and water. Remove contaminated clothing.

Seek medical attention if irritation or symptoms persist.

Contact with eyes: Rinse eyes immediately with plenty of water, keeping the eye open.

Seek medical attention.

Ingestion: Do not induce vomiting or give water to drink. Seek medical attention

and show product label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Irritating to respiratory system.

Skin contact Irritating to skin.

Contact with eyes Irritating to eyes

Ingestion May cause suffocation and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

As a general rule, and in all cases of doubt or when symptoms persist, always seek medical attention.

## 5. Fire fighting measures

## 5.1 Extinguishing media

5.1.1. Suitable extinguishing media: Use extinguishing media appropriate the surrounding fire

conditions. Use as appropriate: water spray, dry extinguishing media, foam and carbon dioxide.

5.1.2 Unsuitable extinguishing media: No specific recommendations.

## 5.2. Special hazards arising from the mixture

Due to heat pressure in the aerosol-can is rising and there is a risk for explosion. In contact with fire product forms toxic fumes. Explosive propellant-air mix can be formed.

**5.3. Advice for fire-fighters**No specific recommendations.

#### 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear protective clothing, goggles and protective chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Avoid contact with skin and eyes. Do not inhale fumes. Use a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387), when you use product in the room which has a poor ventilation

## 6.2 Environmental precautions:

Spillages shall be absorbed by sand or cloths and stored in suitable container, or allow the foam to solidify. The waste must be handled in accordance with legal requirements.

#### 6.3 Methods and material for containment and cleaning up

Fresh foam can be removed with acetone, cured foam only mechanically.

#### 7. Handling and storage

### 7.1 Precaution for safe handling:

During operation, note that the product contains a flammable gas. Keep away from heat. Do not break or burn even after use. Should not be sprayed on a open flame or any incandescent material.

7.1.1. Protective measures Ensure good ventilation. Keep away from heat. Keep away from sources

of ignition- No smoking. Avoid contact with eyes and skin. Avoid static electricity. Make use of protective goggles and protective chemical resistant gloves classified under Standard EN374: protective gloves

against chemicals and microorganisms.

## 7.1.2. Advice on general occupational hygiene

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

# PENOSIL EasyGun Foam All Season

### 7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep in a cool, dry, well-ventilated area in an upright position away from direct sunlight and other heat sources. Do not store in the direct sunlight and not more than +50 °C. Storage: temperature +5°C to +30 °C.

## 7.3. Specific end use(s)

Foam is used for installation of doors and windows, insulation and fixation of tubes, filling of holes and gaps, fixation of wall panels and roof stones, and for thermal insulation. Adheres well to most building materials, with the exception of teflon, polyethylene and silicon surfaces. Cured foam is sensitive to UV-light and direct sunlight.

## 8. Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit value

Components	CAS-No.	Type form of exposure	Control parameters
Dimethyl ether	115-10-6	TWA	1920 mg/m <sup>3</sup> 1000 ppm
Diphenylmethane- 4´,4´-diisocyanate	9016-87-9	No information	0,05 mg/m <sup>3</sup> 8 hours 0.005 ppm 8 hours
Propane	74-98-6	No information	Short time: 2000 mg/m³, 1100 ppm Long time: 1500 mg/m³, 800 ppm
Butane	106-97-8	No information	Short time: 1810 mg/m <sup>3</sup> , 750 ppm Long time: 1450 mg/m <sup>3</sup> , 600 ppm

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

8.2.2. Individual protection measures, such as personal protective equipment Eye/face protection:

During the work make use of protective goggles

Skin protection: During the work make use of protective chemical resistant gloves

classified under Standard EN374: protective gloves against chemicals

and microorganisms.

Respiratory protection: Use the product only in well-ventilated rooms. Do not inhale fumes.

When using in poorly ventilated area, wear a suitable filter of the mask (ie

type A1 in accordance with EN 14387).

8.2.3. Environmental exposure controls Do not let into environment. May cause long-term adverse

effects in the aquatic environment.

## 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

**Appearance** Aerosol Colour Pale beige Odour Characteristic pН Not applicable Melting point / freezing point Not relevant Boiling point Over +100 °C Flash point Below -20 °C Evaporation rate Not relevant Flammability Above +100 °C

Explosion limits

Low: 2 % vol, high: 10% vol.

Vapor pressure

Low: 2 % vol, high: 10% vol.

5 Bar/+20 °C 10 Bar/+50 °C

Vapor density Not applicable

SAFETY DATA SHEET

PENOSIL EasyGun Foam All Season

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

## PENOSIL EasyGun Foam All Season

Relative density 1.1 g/ml/+20 °C Solubility in water insoluble

Solubility in other solvents

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

In acetone soluble

Not applicable

+ 200 °C

Viscosity ca 500 cP/+20 °C

Explosive properties Contains flammable gases.

Oxidizing properties Not applicable **9.2. Other information** Lack of data

## 10. Stability and reactivity

**10.1. Reactivity**The mixture is not reactive under recommended storage and handling

conditions (see section 7).

**10.2. Chemical stability**The mixture is stable under recommended storage and handling

conditions (see section 7).

**10.3. Possibility of hazardous reactions** In case of fire, the product can create corrosive and hazard

gases.

## 10.4 Conditions to avoid:

An aerosol container is under pressure, do not expose to heat. Do not store in the sun, and not more than +50 °C. Do not break or burn even after use. Should not be sprayed on a open flame, or any incandescent material.

10.5. Incompatible materials: No data available

**10.6. Hazardous decomposition products:** In case of fire, the product can create corrosive and hazard gases.

## 11. Toxicological information

#### 11.1. Information on toxicological effects

11.1.1. Substances

11.1.1.1. The relevant hazard classes for which information shall be provided are:

#### (a) Acute toxicity

	Dimethyl ether	Diphenylmethane-4',4'-	Isobutane
		diisocyanate	/ propane
Acute Oral	Not applicable	LD50 (rat): > 2.000 mg/kg	Not
toxicity			applicable
Acute Dermal	Not applicable	Not applicable	Not
toxicity			applicable
Acute Inhalation	LC50 (rat): 164 000 ppm	LC50 (rat): 490 mg/m <sup>3</sup> 4h	Not
toxicity	Respiratory effects Anaesthetic	Tested substance:	applicable
-	effects Central nervous system	Aerosol	
	depression narcosis Cardiac	Saturated vapour concentration at	
	irregularities Coma.	25 °C: 0,09 mg/m <sup>3</sup>	

#### (b) Skin corrosion / irritation

	Dimethyl ether	Diphenylmethane-4´,4´-	Isobutane /
		diisocyanate	propane
Skin	Not tested on animals	Rabbit	No skin
irritation	Classification: Not classified as irritant	Result: No skin irritation	irritation
	Result: No skin irritation	Method: OECD test guide	
	Not expected to cause skin irritation based on	404	
	expert review of the properties of the substance.		

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

# PENOSIL EasyGun Foam All Season

(c) Serious eye damage / irritation

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Eye	Not tested on animals	Rabbit	No eye
irritation	Classification: Not classified as irritant	Result: No eye irritation	irritation
	Result: No eye irritation	Method: OECD test guide	
	Not expected to cause eye irritation based on	405	
	expert review of the properties of the substance.		

(d) Respiratory or skin sensitization

(a) Hoopingtory or our constitution				
	Dimethyl ether	Diphenylmethane-4',4'-	Isobutane /	
		diisocyanate	propane	
Sensitization	Not tested on animals	Result: May cause	No	
	Classification: Not a skin sensitizer	sensitization by inhalation	sensitization	
	Not expected to cause eye irritation	and skin contact	effect	
	based on expert review of the	Isocyanate vapor may cause		
	properties of the substance.	asthmatic allergy		

(e) Germ cell mutagenicity

	Dimethyl ether	Diphenylmethane-4 ´,4´-diisocyanate	Isobutane / propane
Germ cell mutagenicity	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.	Lack of data	Not applicable

(f) Carcinogenicity

	Dimethyl ether	Diphenylmethane- 4',4'-diisocyanate	Isobutane / propane
Carcinogenicity	Animal testing did not show any carcinogenic effects.	Lack of data	Not applicable

(g) Reproductive toxicity

(3)	Dimethyl ether	Diphenylmethane-4 ´,4´-diisocyanate	Isobutane / propane
Reproductive	No toxicity on reproduction	Lack of data	Not
toxicity	May cause cardiac arrhythmia. Rapid		applicable
	evaporation of the liquid may cause frostbite.		

(h) STOT-single exposureLack of data(i) STOT-repeated exposureLack of data

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

# PENOSIL EasyGun Foam All Season

## 12. Ecological information

12.1. Toxicity

12.1. TOXICITY	Dimethyl ether	Diphenylmethane-4´,4´-	Isobutane /
	, , , , , , , , , , , , , , , , , , , ,	diisocyanate	propane
Toxicity to fish	LC50 /96h/ Poecilia reticulate	LC50 /96h/ danio rerio: > 1.000	Not
	(guppy): > 4000 mg/l	mg/l	applicable
		Method: OECD test guide 203	
Toxicity to	EC50 /48h/ Daphnia: > 4000 mg/l	EC50 /24h/ Daphnia magna: >	Not
aquatic	LC50 /48h/ Daphnia: 755,5 mg/l	1.000 mg/l	applicable
invertebrates	-	Method: OECD test guide 202	
Chronic	Due to its physical properties, there	Lack of data	Lack of data
toxicity to fish	is no potential for adverse effects.		
Toxicity to	Lack of data	EC50 /3h/ activated sludge:	Lack of data
bacteria		>100 mg/l	
		Method: OECD test guide 209	

12.2. Persistence and degradability

12121 1 didictined and degradability					
	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane		
Persistence and degradability	Method: Closed Bottle test According to the results of tests of biodegradability this product is not readily biodegradable.	Biodegradability 28 days 0 %. Method: OECD test guide 302 C	Not applicable		

12.3. Bio-accumulative potential:

	Dimethyl ether	Diphenylmethane-4´,4´- Isobuta	
		diisocyanate	propane
Bioaccumulation	No data available	No data available	Not applicable

12.4. Mobility in soil:

12.41 mobility in com					
	Dimethyl ether	Diphenylmethane-4',4'-	Isobutane / propane		
		diisocyanate			
Mobility in soil	Koc: 7,759	No data available	Not applicable		

12.5. Results of PBT and vPvB assessment:

12.0. Nesalts of 1 D1 dild 41 4D descessificate.				
	Dimethyl ether	Diphenylmethane-4 ´,4´-diisocyanate	Isobutane / propane	
PBT and	This substance is not considered to be	No data available	Not	
vPvB	persistent, bio accumulating nor toxic (PBT).		applicable	
assessment	The substance is not considered to be very			
	persistent nor very bio accumulating (vPvB).			

## 12.6. Other adverse effects

Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Ozone depletion potential: 0	Not applicable	Not applicable
Global warming potential (GWP): 1		

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

## PENOSIL EasyGun Foam All Season

## 13. Disposal considerations

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal: The product and packages must be handled in accordance with

national and local requirements.

13.1.2. Waste treatment options: Foam bottles are recyclable.

13.2. Additional information No specific recommendations.

14. Transport information

**14.1 UN number** 1950 **14.2 Packing Group** Not known

14.3 Road ADRInflammable aerosol Class 2/5F14.4 Railway RIDInflammable aerosol Class 2/5F

14.5 Transport by sea GGVSee/IMDG-Code Aerosol Class 2

14.6 Air transport ICAO-TI/IATA-DGR

## 15. Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

#### 15.2. Chemical safety assessment

Chemical safety assessment has been carried out for dimethyl ether and still at work for diphenylmethane-4′,4′-diisocyanate.

## 16. Other information

## 16.1. Date of preparation of the latest version of the SDS

Written in the beginning of the safety data sheet.

## 16.2. Abbreviations and acronyms

TWA: Time Weighted Average

LC50: Lethal Concentration Medium

EC50: effective Concentration Medium

STOT: Specific target organ toxicity

PBT: Persistent, bioaccumulativ and toxic

vPvB: very persistent very bioaccumulative

Acute Tox.4: Acute Toxicity: inhaled- Category 4

Carc. 2: Carcinogenicity- Category 2

Eye Irrit. 2: Serious eye damage/ eye irritation- Category 2

Resp. Sens. 1: Respiratory sensitization- Category 1

Skin Irrit.2: Skin corrosion/irritation- Category 2

Skin Sens. 1: Skin sensitization- Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure): inhalation- Category 2

STOT SE 3: Specific target organ toxicity (single exposure): inhalation- Category 3

Flam. Gas 1: Flammable Gas- category 1

Press. Gas: Gases under pressure

Aquatic Acute 1: Aquatic Acute- Category 1

Aquatic Chronic 1: Aquatic Chronic- Category 1

## 16.3. Key literature references and sources of data

The safety data sheet meets the requirements of the European Parliament and Council Regulation (EC) No.1907/2006, (EC) Regulation 453/2010 and the Chemicals Act of the Republic of Estonia and regulation No 130 of Minister of Social Affairs.

## 16.4. Classification and classification procedure used for mixtures

16.5. Relevant R-phrases and/or H-statements (specified in clause 3)

SAFETY DATA SHEET

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET

## PENOSIL EasyGun Foam All Season

## **According Directive 67/548/EEC**

R12 Extremely flammable

R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitization by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R53 May cause long-term adverse effects in the aquatic environment

R64 May cause harm to breast-fed babies

R66 Repeated exposure may cause skin dryness or cracking

## According Regulation 1272/2008 (CLP)

H220 Extremely flammable gas

H280 Contains gas under pressure; may explode if heated

H315 Cause skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H332 Harmful if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

H351 Suspected of causing cancer

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure if ihaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**16.6. Training advice**No specific recommendations. **16.7. Further information**No specific recommendations.